

P1000 TECHNICAL SPECIFICATIONS

ALL MEASUREMENTS ARE WITH 230V / 50 HZ MAINS POWER

CONTINUOUS OUTPUT POWER (WATTS PER CHANNEL)

ALL CHANNELS DRIVEN	20HZ - 20KHZ, 8Ω	135 WPC	945KW TOTAL
	20HZ - 20KHZ, 4Ω	210WPC	1.47KW TOTAL
ONE OR TWO CHANNELS DRIVEN AT 1KHZ, 8Ω		190 WPC	
	1KHZ, 4Ω	250 WPC	
	1KHZ, 3.2Ω	300 WPC	

PEAK OUTPUT CURRENT CAPABILITY

>20.5 AMPS PER CHANNEL

TOTAL HARMONIC DISTORTION

AT ANY LEVEL UP TO RATED POWER, INTO 4 OR 8Ω

<0.08% 20HZ - 20KHZ, TYPICALLY <0.007% AT 1KHZ

FREQUENCY RESPONSE

+/- 0.2DB 20HZ - 20KHZ

-1 DB AT 10HZ AND 20KHZ

RESIDUAL HUM AND NOISE

REF FULL POWER

-110DB A WEIGHTED, OR 100DB CCIR

VOLTAGE GAIN

USER SELECTABLE

A X31.5DB

B X29DB

C X26DB

INPUT IMPEDANCE

22KΩ IN PARALLEL WITH 180 PF

OUTPUT IMPEDANCE

50M Ω AT 20HZ, 1KHZ

80M Ω AT 20HZ

GENERAL

WXDXH (INCLUDING FEET) 430 X 400 X 133MM

POWER CONSUMPTION 2.2KW MAX

WEIGHT (NET) 18KG

E&OE 08/05